

Interior Wood Lacquer

PRODUCT DATA

Description

Water-based acrylic lacquer for interior timber surfaces including furniture, floors, and joinery. Provides a clear, non-yellowing finish with resistance to alcohol spills and heat (ring resistant). Designed for domestic and light traffic use. Quick drying, low odour, and easy to apply. Suitable for new or previously coated wood.

Important: Please note this product should not be used when the floor temperature is below 10 degrees centigrade or in an area subjected to cold drafts, this will affect the performance of the lacquer causing a white milky finish.

Area of use

Domestic flooring or light traffic areas

Substrates

Wood

Packing

2.5 litres and 5 litres (2.5L only avail semi-matt)

Physical Constants

Colour:	Clear
Finish:	Matt/Satin/Gloss
Volume solids:	40%
Theoretical spreading rate:	18 – 20 sq.metres per litre
Flash point:	N/A
Specific gravity:	1.02
Dry to touch:	15 – 20 minutes
Overcoating time:	2 – 3 hours

****The theoretical spreading rate** has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. **The physical constants** are subject to normal manufacturing tolerances.*

Application Details

Application method:	Brush
Thinner:	Water
Cleaning of tools:	Water

<u>Surface condition</u>	The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.
---------------------------------	--

Please refer to the Material Safety Data Sheet for further information.

SAFETY: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

For additional guidance please contact your local Technical Sales Representative.

SAFETY:Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.

Flag Paints LTD T/A Flag Formulations 8 Springfield Road, Burnham on Crouch, CM0 8UA, Tel:+44 1621 785173